

Project number	
Purchase order	
Requisition	

# DATASHEET

## PNEUMATIC PRESSURE SWITCH

DATE	REV	BY	CHK	APP	SUBJECT OF REVISION

Doc. nr.:

AMBIENT CONDITIONS				ACCESSORIES (only if requested on next page)			
1		Units		59	Manifold type	Manifold mat.	
2	Ambient temperature	unit	Min.    Max.	60	Manifold instrument connection		
3	Humidity range	unit		61	Manifold process connection		
4	Altitude	unit		62			
5	Corrosivity cat. (ISO 12944-2)			63			
6	Hazardous area classification			64			
7	Minimum protection type			65			
8				66			
9				67			
SENSOR ELEMENT				CHEMICAL SEAL (only if requested on next page)			
10	Element type			68	L-press. side	Seal type	
11	Type of pressure			69		Seal mounting	
12	Element material			70		Diaphragm exten. length	
13	Process/chem. seal connect. mat.			71		Seal wetted parts mat.	
14				72		Seal model number	
15				73	H-press. side	Seal type	
<b>SWITCH</b>				74		Seal mounting	
16	Switch type			75		Diaphragm exten. length	
17	Pneumatic function			76		Seal wetted parts mat.	
18	Pressure supply	unit		77		Seal model number	
19	Supply fitting			78		Seal upper mat.	Flange mat.
20				79	Capillary length	unit	L-side    H-side
21				80	Capillary internal diameter		
<b>ENCLOSURE</b>				81	Capillary material		
22	Enclosure material			82	Capillary armor material		
23	Ingress protection			83	Capillary fill fluid		
24	Hazardous area class. + protect.			84			
25	Cable gland entry			85			
26				86			
27				87			
28				88			
29				89			
30				90			
31				91			
32				92			
33				93			
34				94			
35				95			
36				96			
37				97			
38				98			
39				99			
40				100			
41				101			
<b>NOTES</b>				102			
42				103			
43				104			
44				105			
45				106			
46				<b>SUPPLIER INFORMATION</b>			
47				107	Vendor		
48				108	Manufacturer		
49				109	Vendor stamp		
50				110			
51				111			
52				112			
53				113			
REFERENCE DOCUMENTS/APPLICABLE SPECIFICATIONS				RELIABILITY DATA			
54	Number	Rev	Title	114	Fail safe detected (FIT)		
55				115	Fail safe undetected (FIT)		
56				116	Fail dangerous detected (FIT)		
57				117	Fail dangerous undetected (FIT)		
58				118	Safe failure fraction (SFF) (%)		



**PROJECT**

Project number  
Purchase order  
Requisition

Pos.	TAG N°	Process fluid	Range	Dead band	Dead band size	Process Connection	Number of switches	Switch 1		Switch 2		Options	Approvals	Pressure switch model
								Setpoint	Direction	Setpoint	Direction			
1														
2														
3														
4														
5														
6														
7														
8														
9														
10														
11														
12														
13														
14														
15														
16														
17														
18														
19														
20														
21														
22														
23														
24														
25														

- |  |   |
|--|---|
| <p>27 <b>Options</b></p> <p>28 A. Cleaned for oxygen service</p> <p>29 B. Factory adjusted setpoint(s)</p> <p>30 C. Chemical seal</p> <p>31 D. Manifold</p> <p>32 E1. Mounting directly on process</p> <p>33 E2. Mounting bracket for wall mounting</p> <p>34 E3. Mounting bracket for 2" pipe</p> <p>35</p> <p>36</p> <p>37</p> <p>38</p> <p>39</p> <p>40</p> | <p><b>Approvals</b></p> <p>A. EC Declaration of conformity</p> <p>B. ATEX certificate</p> <p>C. PED certificate</p> <p>D. SIL2 certificate</p> <p>E. NACE MR0175 / ISO 15156 certificate</p> <p>F. Material certificate per EN 10204 3.1 (sensor element)</p> <p>G. Material certificate per EN 10204 3.1 (chemical seal)</p> |
|--|---|

Doc. nr.: